


●● sueno pro R



- Tinnitus-Module
- 9 WDRC-Channels
- Up to 4 Programs
- Rocker Switch (programmable)
- Low Battery Indicator
- Start-up Delay
- Data Logging
- nanoShield
- Option: Power Sleeve
- Accessories: Receiver Unit S, Domes, Concha Clip, Wax Guard

Technical Data

	EN 60118-7:2005 (2 cm ³ -coupler)	EN 60118-0/A1:1994 (Ear Simulator)	ANSI S3.22-2014 (2 cm ³ -coupler)
Operating Voltage	1.30 V	1.30 V	1.30 V
Battery Current	1.05 mA	1.05 mA	1.05 mA
Battery Type	312	312	312
Average Battery Life (Zinc-Air)	130 h	130 h	130 h
Tinnitusmasker			
Noise Level (RMS)	70	79	70
Frequency Range	100 Hz–8000 Hz	100 Hz–8000 Hz	100 Hz–8000 Hz



Standard



Programming

Cable: Cable set J or K
 Battery: without Battery
 Progr.-Box: HI-PRO/HI-PRO II
 HI-PRO USB
 NOAHlink
 Software: audifit 5.6

All curves are measured with 2cm³-coupler (EN 60318-4:2010) in reference setting.

